

INSTALLATION INSTRUCTIONS

Item#P198

READ AND SAVE THESE INSTRUCTION

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER BEFORE INSTALLATION
AVERTISSEMENT! COUPER LE COURANT AUNIVEAU DE FUSIBLES OU DU DISJONCTEUR

ASSEMBLING THE FIXTURE (Fig. 1)

1. Shut off the power at the circuit breaker box (avertissement! couper le courant au niveau des fusibles ou du disjoncteur) and remove the old fixture, including the mounting hardware.
2. Carefully remove the fixture from the carton and check that all parts are included as shown in the illustration.
3. Thread rod (J) to the nipple (I) at the bottom of housing (H).
4. Carefully pass the fixture wires through rod (F) and connect the rod (F) to the Nipple (G) at top of the housing (H).
5. Pass the fixture wires through the nipple (E) and secure rod (F) to the nipple (E)
6. Secure mounting plate (A)(part#A-021R-118) to the junction box with screws (B) (Size:8-32*1/2"L)

CONNECTION THE WIRES (Fig. 2)

7. At this point, connect the electrical wire as shown in Fig. 2, making sure that all wire connectors are secured. If your outlet has a ground wire (green or bare copper), connect the fixtures ground wire to it. Otherwise, connect the fixture ground wire directly to the circular strap using the green screw provided. After wires are connected, tuck them carefully inside the junction box.

FINISHING THE INSTALLATION (Fig.1)

8. Align canopy (D) to mounting plate (A) and secure with screws (C).
9. Align the glass shade (L) to nipple (K). Align decorative cap (P) to nipple (K) and secure with finial (Q).
10. Install the bulbs (3- 100W A19) (Not Included). **(DO NOT EXCEED THE SPECIFIED WATTAGE!) (NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE)**

Your installation is now complete. Return power to the Outlet Box and test the fixture.

IMPORTANT: FIXTURE SHOULD BE INSTALLED BY A QUALIFIED ELECTRICIAN TO ENSURE PROPER WIRING AND INSTALLATION.

