

ADJUSTABLE WALL WASH

Creates a low, even light spread to illuminate shrubs, plants or textured wall surfaces to silhouette special details.

SPECIFICATIONS

Housing Durable die-cast aluminum construction. Clear polycarbonate shield provides high impact resistance and moisture protection.

Finish Textured Architectural Bronze, Textured Black, Textured Midnight Spruce™

Wiring 46" of usable #18-2, SPT-1-W leads. Cable connector supplied with fixture. 12-Volt S-8 wedge socket.

Light Bulb 24.4-W. Max. 3156K (15599CLR) (nominal at 12-Volts) supplied. Can also use 18.5-W. 3155K (15598CLR).

15961AZT6

314"

15361

Mounting Accessories Included 8" In-ground stake

Optional Mounting Accessories 15651, 15652 or 15653 – Stems (must use 15649 stem coupler) 15601 – Surface Mounting Flange 15607 – Tree/Surface Mounting Bracket

Bulk Pack

15961AZT6 – Bulk Pack includes 8" ground stakes

Bulk Pack Pre-wired with Universal Connector 159614AZT6 with 25' of 16-gauge cable lead for use with Pro Series IV Junction

Korea Design Registration Number 126685

use with Pro Series LV Junction

U.S. Patent No. Des. 330,603 Canada Patent No. 69176

Footcandles/Distance from Fixture Center

Distance from Wall	O	1'	2	3'	4'	5'	6	7'	8'	9	
4"	4.9	3.6	25	1.6	1.0	.70	.40	.30	.15	.10	
8'	1.2	1.1	.90	.78	.63	.50	40	.33	.25	.20	I