

MR-16 ACCENT LIGHT

Larger 41/2 diameter for wider light spread along walls, shrubs and trees.

SPECIFICATIONS

Housing Durable die-cast aluminum construction. (BR and BBR versions are die-cast brass). Heat-resistant flat glass lens fully sealed.

Finish Textured Architectural Bronze, Beach, Brass, Bronzed Brass, Textured Black, Textured Midnight Spruce™

Wiring 35" of usable #18-2, SPT-1-W leads. 12-Volt porcelain. bi-pin socket.

Light Bulb 75-W. Max. MR-16 not supplied*

Mounting Accessories Included 8" In-ground stake

Optional Mounting Accessories

15656, 15657 or 15658 - Stems

15649 - Stem Coupler

15601 - Surface Mounting Flange

15607 - Tree/Surface Mounting Bracket

Optional Lens Accessories

15680 BK - Louver

15687 BL - Blue Filter

15691 FRO - Frosted Lens


15692 LIN - Linear Lens

Bulk Pack 15381AZT6, 15981AZT6 includes 6 fixtures and 6 (8") In-ground black stakes

Bulk Pack Pre-wired with Universal Connector 15981AZT6 with 25' of 16-gauge cable lead for use with Pro Series LV Junction

*See pages 119-121 for more light bulb options and light bulb photometrics.












15381 BR









15381 15981AZT6