



15088 BK
15388 BK
15988 BK6

36-WATT PAR 36 WELL LIGHT

Versatile design with reversible support sleeve to accommodate uplighting when flush mounted or angled lighting effects when semi-recessed. Stainless steel yolk design holds lamp securely at desired angle.

SPECIFICATIONS

Housing Stainless steel yolk with silicone rubber lamp support clips. Heavy-duty polycarbonate ground support sleeve.

Finish Black

Wiring 42" of usable #18-2, SPT-1-W leads. Cable connector supplied with fixture. Supply wire with lugs attach directly to PAR 36 light bulb screw terminals.

Light Bulb 36-W. Max. PAR 36 (not supplied with 15088 BK and 15088 BK12)

Optional Lens Accessories
 15689 BK – Lens Cover

Bulk Pack

15088 BK12 includes 12 fixtures 15988BK6


Bulk Pack Pre-wired with Universal Connector
 15988BK6 with 25' of 16-gauge cable lead for use with Pro Series LV Junction

One Pack 15388 BK includes 35-W. PAR 36 light bulb

UL listed. Includes silicone rubber lamp support clips.

U.S. Patent No. Des. 5,230,559
 Korea Patent No. 126459

***See pages 119–121 for more light bulb options and light bulb photometrics.**



15088/15388



Lens Accessory 15689 BK available for Well Light 15088 and 15388. Heat-resistant glass lens provides protection from sprinklers and lawn debris.



15988BK6