

New**SUMMER 09****15815 AZT****Featuring High-Low Setting****15815 BE****15815 BKT**

LED SIDE MOUNT

LED technology is combined with a side mount design for more directional lighting, without glare. Coordinates with matching LED deck light 15765 on page 80.

Housing Aluminum

Finish Textured Architectural Bronze, Beach or Textured Black

Light Source Integrated LEDs and Driver

Power Usage at 12V AC Input

VA Total: 5.8 High, 4.0 Low

Watts Total: 4.1 High, 2.5 Low

Multiply fixture VA by the number of fixtures used to determine size of transformer

Wiring 50" of usable #18-2, SPT-1-W leads.

Cable connector supplied.

Mounting Accessories Included

8" In-ground stake

Optional Mounting Accessories

15601 – Surface Mounting Flange

15607 – Tree/Surface Mounting Bracket

Optional Lens Accessories

15695 CLR – Lens

Separate driver is not required with this series.
Not intended for use with electronic transformers.

Also available with a Xenon light source.
See 15315 on page 62.

Fixture Photometric (fc) – HI Setting

Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'
Footcandle	31.5	17.2	8.7	2.5	1.2	0.5	-	-	-

Fixture Photometric (fc) – Low Setting

Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'
Footcandle	21.3	12	4.1	1.7	0.7	0.2	-	-	-

