

EXIT SIGNS

Wall or ceiling mounted •



Specifications:

Description:

LED exit sign with red letters.

Construction:

- White (-30)
- Flicker-free dimming to 10% brightness with most ELV type dimmers (See Dimming Notes)

Performance:

| | |
|---------------------|----------------------|
| Number of Modules | |
| Input Power | |
| Input Voltage | 120V |
| Input Frequency | 60Hz |
| Lumens/LPW | / (LM-79) per module |
| CCT | |
| CRI | |
| Life | (L70/TM-21) |
| EMI/RFI | |
| Min. Start Temp | |
| Max. Operating Temp | |
| Warranty | 1 year warranty |
| Labels | |

PE008-30

Images:



Dimensions:

Width: 11.6"
Height: 8.2"
Depth: 4.3"

Catalog number:

| | |
|-------|------------|
| Base | Finish |
| PE008 | 30 - White |

PE008-30

Dimming Notes:

PE008 is designed to be compatible with many Electronic Low Voltage (ELV-Reverse Phase) controls.

The following is a partial list of known compatible dimmer controls:

Electronic Low Voltage ELV Reverse Phase Controls

| | | |
|---------|---------------|--------------------------|
| Lutron | Diva Series | (Part Number DVELV-300P) |
| Lutron | Nova T Series | (Part Number NTELV-300) |
| Lutron | Vierti Series | (Part Number VTELV-600) |
| Lutron | | (Part Number MAELV-600) |
| Lutron | | (Part Number SPELV-600) |
| Leviton | | (Part Number AWRMG-EAW) |
| Leviton | | (Part Number 6615-P) |

Digital type dimmers are not recommended.

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.