

97314S: 15w 120V PAR30L Medium Base LED 3000K





Dimensions:

Diameter: 3 25/32" Bulb Type: PAR30L

Length: 4 9/16" Bulb Base: E-26 Medium

Volts: 120 **Watts**: 15

Watts Consumed: 15

Watts Rated: 15

Hours Rated: 50000

Lumens: 720

Bulb Temp: 3000 °K

CRI: 85

Beam Spread: 40

Collection: LED Lamp

Designed to work reliably in Sea Gull decorative and functional lighting including recessed and enclosed luminaires

Produces 725 lumens, consumes 15 watts -equivalent to 75W halogen lamp

15W LED PAR30L Med. base lamp, 3000K, 40 degree beam

Replicates the look, feel and performance of halogen, reduce energy and operating cost by 80%

Long 50,000 hour life for maiteance free operation

Visually pleasing, color accurate illumination; CRI 85, 3000K

Unique optical design for smooth beam pattern without pixelation

Thermally efficient for cooler operation, extended lamp life and for use in recessed luminaires

Dimmable down to 5% with most standard dimmers

Instant-on, no warm up time

Emits no UV or IR, will not heat or fade illuminated objects

Contains no mercury or lead, fully recycleable RoHS compliant

Energy Star compliant, 5 year warranty

While the LED lamp draws as little as 15W continuously, it could have an-in rush current spike and should therefore be treated as a 115W load when sizing dimmers. The recommended maximum number of lamps per an approved 600W dimmer is 5 units. Please refer to list of compatible dimmers located under Additional Information section.

Features:

 This advanced LED technology is carefully designed and selected to consist of the highest quality LED chipsets for superior performance and reliability.

Material List:

Safety Listing:

Safety Listed for Wet Locations Safety Listed for Wet Locations

Instruction Sheets:

UPC #:785652152115

Shipping Information:

Package Type	Product #	Quantity	UPC	Length	Width	Height	Cube	Weight	Frt. Class	UPS Ship
Individual	97314S	1	785652152115	4	4	5.75	0.053	1.1	85	Yes
Master Pack	97314S	6	10785652152112	12.5	8.75	6	0.38	6.7	85	Yes
Shipping Master		24								
NJ Pallet		960		48	40	68.75	76.389	1124		No
NV Pallet		960		48	40	68.75	76.389	1124		No