




# Product Specifications Report

<b>Job Name:</b>		<b>Job Type:</b>	
<b>Comments:</b>		<b>Quantity:</b>	
<b>Product Number: 1174LE</b>		<b>Dimensions:</b>	
 <p><b>1174LE - Fluorescent Non-IC Housing</b></p> <p>New construction fluorescent recessed lighting. UL listed for damp location with one class P HPF Electronic ballast. Bar hanger adjustable to 24". Shown with 1156-15 trim (sold separately).</p> <p>Non-IC Airtight Fluorescent New Construction Recessed Housing. Electronic Ballast, HPF; (Ref. Dim. 1207)</p> <p>Safe - Thermally Protected/Listed for Damp Location: Non-IC housings are approved for use where insulation is kept at least 3" away from housing.</p> <p>Housing Adjustment: Housing adjusts vertically for various ceiling thicknesses.</p> <p>Bar Hanger Locking Tabs: Squeeze tabs with pliers to lock bar hangers in place.</p> <p>Bar Hanger: Break-away bar hangers easily extend and will not fall out of plaster flange, providing sturdy installation.</p> <p>Quick Hit: Integral captive nails included and positioned for fast, easy installation.</p> <p>Trouble-Free Ballast: Provided with integral ballast offering years of trouble-free operation.</p> <p>Junction Box with Integral Romex Connector: Junction box with integral romex connector, quick-push and lock connector and through circuit wiring with 4 in, 4 out #12 wire, saves installation time.</p> <p><b>UPC #:</b> 785652011740      <b>Product Type:</b> Recessed Light</p>		<p><b>Diameter:</b> 4 1/4"      <b>Switch Type:</b> N/A</p> <p><b>Length:</b> 13 1/2"      <b>Mounting Proc.:</b> Other</p> <p><b>Width:</b> 5 1/4"</p> <p><b>Height:</b> 5 5/8"</p>	
		<b>Material List:</b>	
		1 Housing - Steel -	
		<b>Safety Listing:</b>	
		<p>cUL Listed for Damp Locations / Non-IC                  UL Listed for Damp Locations / Non-IC</p>	
		<b>Instruction Sheets</b>	
		English (HC-931)	
<b>Features:</b>			
Energy Star Compliant		Fluorescent	
Title 24			

**Trim**



[11091AT-15](#)

**4" Wall Wash Trim**

White Steel Baffle  
 White Aluminum Reflector  
 White Steel Trim  
 Maximum Wattage:  
 26w 4 - Pin



[11092AT-15](#)

**4" Shower Trim**

Frosted Glass Glass  
 White Aluminum Reflector  
 White Aluminum Trim  
 Maximum Wattage:  
 26w 4 - Pin  
 Suitable For Shower Light



[1152AT-15](#)

**Recessed Trim**

Frosted Glass Glass  
 Polished Aluminum Aluminum  
 Reflector  
 White Steel Trim  
 Maximum Wattage:  
 26w 4 - Pin  
 Suitable For Shower Light



[1153AT-15](#)

**Recessed Trim**

Clear Glass Glass  
 Polished Aluminum Aluminum  
 Reflector  
 White Steel Trim  
 Maximum Wattage:  
 26w 4 - Pin  
 Suitable For Shower Light



[1156AT-14](#)

**Recessed Trim**

White Trim / Baffle Steel  
 Baffle  
 White Steel Trim  
 Maximum Wattage:  
 26w 4 - Pin



[1156AT-15](#)

**Recessed Trim**

Black Steel Baffle  
 White Steel Trim  
 Maximum Wattage:  
 26w 4 - Pin



[1162AT-14](#)

**Recessed Trim**

White Trim / Baffle Aluminum  
 Aluminum Multiplier  
 White Aluminum Trim  
 Maximum Wattage:  
 26w 4 - Pin



[1162AT-172](#)

**4" Multiplier Trim**

Antique Bronze - White  
 Aluminum Reflector  
 White Steel Trim  
 Maximum Wattage:  
 26w 4 - Pin



[1162AT-19](#)

**Recessed Trim**

Metallic Gold Aluminum  
 Baffle  
 White Aluminum Trim  
 Maximum Wattage:  
 26w 4 - Pin



[1162AT-22](#)

**Recessed Trim**

Polished Aluminum  
 Aluminum Baffle  
 White Aluminum Trim  
 Maximum Wattage:  
 26w 4 - Pin



[1162AT-71](#)

**4" Multiplier Trim**

Antique Bronze Aluminum  
 Reflector  
 Antique Bronze Steel Trim  
 Maximum Wattage:  
 26w 4 - Pin



[1162AT-849](#)

**4" Multiplier Trim**

Satin Nickel Aluminum  
 Reflector  
 Satin Nickel Steel Trim  
 Maximum Wattage:  
 26w 4 - Pin



[1162AT-861](#)

**4" Multiplier Trim**

Satin Nickel - White  
 Aluminum Reflector  
 White Steel Trim  
 Maximum Wattage:  
 26w 4 - Pin

**Shipping Information**

Package Type	Quantity	UPC	Length	Width	Height	Cube	Weight	UPS Ship	Label
Individual	1	785652011740	14.5	7.5	9	0.566	3.2	Yes	F E-1 IP
Master Pack	6	10785652011747	22.38	18.78	7	1.703	22.4	Yes	16 E-1 M
NJ Pallet	240		48	40	74	82.222	896	No	
NV Pallet	240		48	40	74	82.222	896	No	